

# digitalized CRT, value and lead-free design

With first-ever one-chip Digital Deflection CPU for superb display, the exclusive High Bright Hot Key for instant brightness enhancement, ideal screen size and lead-free design, the 107S6 delivers an unbeatable mix of performance and value.

## Outstanding front of screen performance

- Philips breakthrough advanced Digital Deflection CPU
- High Bright Hot Key instantly adjusts brightness levels
- XGA 1024 x 768 resolution for sharper display
- Easy-on-the-eyes high-bright, high-contrast tube
- Real flat CRT for natural, distortion and glare-free display
- sRGB ensures color matching between display and printouts

## Great convenience

- Compatibility with PC and Mac platforms

## Green design

- Lead-free display protects your health and our environment
- Lower power consumption than industry average
- MPR-II compliance limits electromagnetic radiation
- Environmentally responsible Energy Star Partner
- Flame retardant case safeguards display from fire



# 17 inch CRT Monitor

## Commercial Specifications

### Picture/Display

- Display Screen Type Real Flat Picture Tube
- Panel Size 17" / 41 cm
- Phosphor P22
- Recommended Display Area 306 x 230 mm (12.0" x 9.0")
- Dot Pitch 0.25 mm
- Horizontal Dot Pitch 0.21 mm
- White Chromaticity, 6500° K  $x = 0.313 / y = 0.329$
- White Chromaticity, 9300° K  $x = 0.283 / y = 0.297$
- Maximum Resolution 1280 x 1024 @ 60 Hz
- Recommended Resolution 1024 x 768 @ 85 Hz
- Factory Preset Modes 8 modes:  
640 x 480 @ 60 Hz, 640 x 480 @ 85 Hz,  
720 x 400 @ 70 Hz, 800 x 600 @ 75 Hz,  
800 x 600 @ 85 Hz, 1024 x 768 @ 75 Hz,  
1024 x 768 @ 85 Hz, 1280 x 1024 @ 60 Hz
- Factory Preload Modes 14 modes
- Video Dot Rate 120 MHz
- Horizontal Scanning Frequency 30 - 71 KHz
- Vertical Scanning Frequency 50 - 160 Hz
- Recommended Refresh Rate 85 Hz
- Screen Enhancements Anti-glare Polarizer,  
Anti-reflection, Anti-static,  
High Brightness,  
High Contrast
- Digital Deflection Yes
- sRGB Yes
- GTF Yes

### Connectivity

- Cables D-sub Video Cable,  
Power Cord
- Sync Input Impedance (ohm) 4.7 k
- Video Input Impedance (ohm) 75
- Video Input Signal Levels 0.7 Vpp
- Video Sync Input Signal Separate Sync
- Video Sync Polarities Positive and Negative
- Cable Connection AC Power in

### Convenience

- Convenience Enhancements Menu Languages,  
On-screen Display
- Monitor Controls Brightness Direct Access,  
Contrast Direct Access,  
High Bright Hotkey, Menu,  
Power On/Off
- OSD Languages English, French, German,  
Italian, Spanish, Portuguese,  
Korean (Simplified Chinese,  
Russian, Turkish for some  
Regions)
- Plug & Play Compatibility DDC 2B  
Windows 98/ME/2000/XP
- Regulatory Approvals CE Mark, FCC-B, UL, CSA,  
MPR-II, Low Emission,  
NUTEK, Energy Star,  
SEMKO, TÜV/GS, TÜV Ergo,  
FDA, EZU, GOST, MEEI,  
PCBC, CCC, BSMI, E2000
- Swivel +/- 90°
- Tilt -5° to 13°

### Accessories

- Included Accessories AC Power Cord
- Optional Accessories Multimedia Base
- User Manual Yes

### Dimensions

- Depth (with base) 424 mm
- Height (with base) 383 mm
- Width (with base) 397 mm
- Temperature Range (Operation) 0°C to 40°C
- Temperature Range (Storage) -25°C to 65°C
- Weight 15 kg

### Power

- Complies With Energy Star, NUTEK, E2000
- Consumption 68 W (Typical)
- Off Mode 1 W
- Power LED Indicator Off, Flashing Green;  
Operation, Green
- Power Supply Built-in

## Product Highlights

### Digital Deflection CPU

An exclusive Philips innovation – the world's first one-chip CRT solution – combines the deflection and the Microcontroller in a single chip to process and control input sync digitally. This innovative technology prevents electronic noise that can harm display quality, reduces display jitter and improves geometry for better front of screen performance.

### High Bright Hot Key

A feature that delivers instant brightness adjustment to the ideal level for viewing text, Internet, game or multimedia applications, providing comfortable viewing and an enhanced experience for each type of application.

### XGA, 1024 x 768 resolution

For graphics monitors, the screen resolution signifies the number of dots (pixels) on the entire screen. For example, a 1024-by-768 pixel screen is capable of displaying 1024 distinct dots on each of 768 lines, or about 786 thousand pixels. XGA provides resolutions of 640 by 480 or 1024 by 768 pixels.

### High-bright, high-contrast tube

A CRT tube designed to increase display brightness and contrast by increasing the CRT ray gun's beam current.

### Real flat CRT display

Philips advanced flat CRT technology that minimizes glare while reducing reflection and distortion, delivering natural viewing and display quality superior to that of conventional CRTs.

### sRGB ready

Calibrated RGB that is optimized for the vast majority of computer peripherals, monitors, operating systems and browsers, allowing accurate color mapping with very little data overhead.

### Two platform compatibility

The ability to work with a variety of platforms; Philips monitors are compatible to connect with PC by employing a VGA connection and connect with Macintosh.

### Lead free

Lead-free display products are designed and produced in compliance with strict European Community Restriction of Hazardous Substances (RoHS) standards that restrict lead and other toxic substances that can harm health and the environment.

### Energy efficiency

Reduction of the electrical power required to operate a device to achieve real savings.

### MPRII compliant

The world standard stringent levels setting of electromagnetic radiation emitted by monitors.

### Energy Star Partner

Power conservation requirements set forth by the Environmental Protection Agency of the U.S. government.

### Flame retardant case

A system of limiting accidental fires by engineering flame retardants into the monitor's case.

Trademarks owned by Royal Philips Electronics  
2004 © Royal Philips Electronics - All rights reserved  
As an Energy Star partner, Philips has determined that this product meets the Energy Star guidelines for energy efficiency.  
Microsoft and Windows are registered trademarks of Microsoft Corporation.  
All data subject to change without notice  
Release date: October 2004, v.3  
www.philips.com

