17inch LCD Monitor

the best productivity solution

When getting the job done demands outstanding performance, Philips 170P5 delivers superior ergonomics and excellent front-of-screen performance for clear display. Plus good reliability and energy savings of 20 percent above the industry average.

Outstanding front of screen performance

- LightFrame[™] delivers best-ever sharpness and brightness
- Zero Bright Dot[™] eliminates LCD bright dot defects
- Fast response time capable of handling fast moving pictures
- + SXGA 1280 \times 1024 resolution for sharper display
- Dual Input accepts both analog VGA and digital DVI signals
- Easy plug and play DVI ensures true digital experience
- sRGB ensures color matching between display and printouts

Maximum comfort for maximum productivity

- Audio speakers built into a display device without clutter
- Screen height adjustable for ideal viewing angle
- Screen pivot for portrait and landscape options
- Screen tilt and swivel adjustment for ideal viewing angle
- Cable management for a tidy work space

Best total cost of ownership solution

- Up to 20% lower power consumption than industry average
- Kensington anti-theft lock secures monitor against theft

Great convenience

- Embedded power supply eliminates external power adaptors
- VESA mounting pattern for easy wall mounting of display
- FlexiHolder to hold notes, cards, and photos









170P5ES

17inch I CD Monitor

Commercial Specifications

Picture/ **Display**

- LCD Panel Type
- Panel Size
- Effective Viewing Area
- Pivel Pitch
- Brightness (nits)
- Contrast Ratio
- Display Colors
- Viewing Angle (C/R > 5)
- Response Time

- Maximum Resolution
- Recommended Resolution
- Factory Preset Modes
- User Definable Modes
- Refresh Rate (V) • Picture Enhancement
- sRGB

Connectivity

- Signal Input
- I/O interface on pad

Convenience

Built-in Audio

Convenience Enhancements

- Monitor Controls
- OSD Languages
- Other Convenience Features
- Plug & Play Compatibility
- Regulatory Approvals
- Swivel
- Tilt
- VESA Mount

Accessories

- User Manual
- Pivot & Portait User Pack
- Included Accessories
- PHILIPS

1280 x 1024 pixels, Anti-glare Polarizer, RGB Vertical Stripe 17"/ 43cm 337.9 x 270.3 mm 0.264 x 0.264 mm 260 500.1 16.7 M - Horizontal : 160° - Vertical · 140° 16 ms • White Chromaticity, 6500° K x = 0.313 / y = 0.329• White Chromaticity, 9300° K x = 0.283 / y = 0.2971280 x 1024 @ 75Hz 1280 x 1024 @ 60Hz 15 modes 16 modes Horizontal Scanning Frequency 30 - 82 KHz 56 - 76 Hz LightFrame ™

> Analog (VGA), DVI-D, PC Audio in Headphone Jack

2W RMS x 2 (32 PMPO)

Yes

speakers On-screen Display Auto, Brightness control, Left/Right, LightFrame, Menu (OK), Power On/Off, Up/Down, Volume control English, French, German, Italian, Simplified Chinese, Spanish Kensington Lock DDC/CI. sRGB. Windows 98/ME/2000/XP CE Mark, E2000, FCC-B, UL, CSA, MPRII, Low Emission, NUTEK, Energy Star, SEMKO, EMC, TCO'03, TCO'99, TÜV/GS, TÜV-Ergo +/- 45° -5° to 25° 100 mm x 100 mm

Yes Yes AC Power Cord. Audio

Cable, DVI-D Cable,

VGA Cable

 Power I FD Indicator • Power Supply

Complies With

Consumption

• Sleep Mode

Dimensions

• Depth (with base)

Height (with base)

• Width (with base)

Relative Humidity

• MTBF

• Weight

Power

Height Adjustment Range

Temperature Range (Storage)

Trademarks owned by Royal Philips Electronics 2004 © Royal Philips Electronics - All rights reserved As an Energy Star partner, Philips has determined that this product meets the Energy Star guidelines for energy efficiency.

Microsoft and Windows are registered trademarks of Microsoft Corporation.

All data subject to change without notice Release date: January 2004 www.philips.com

Product Highlights

Zero Bright Dot™

Bright dots are defects in a LCD panel once thought to be an inevitable part of the manufacturing process. With Zero Bright Dot[™], Philips monitors are guaranteed without dot defects.

sRGB ready

Calibrated RGB that is optimized for the vast majority of computer monitors, operating systems and browsers, so as to allow accurate color mapping with very little data overhead.

Adjustable height

The ability to set your monitor to the most pleasurable viewing height. Height adjustment makes computer work more comfortable and reduces fatigue or eyestrain, even when you spend long hours working on the computer. It makes you more productive.

SXGA, 1280 x 1024 resolution

For graphics monitors, the screen resolution signifies the number of dots (pixels) on the entire screen. For example, a 1280-by-1024 pixel screen is capable of displaying 1280 distinct dots on each of 1024 lines, or about 1.3 million pixels.

LightFrame™

An intelligent and revolutionary technology for enhancing monitor's brightness, sharpness, contrast and color. Images enhanced by LightFrame[™] are lively, realistic, clear, attractive and colorful.

Screen pivot

Enables use of a monitor in both landscape and portrait orientations. In order to have a better view of the image displayed on screen you can change orientation effortlessly by simply holding the monitor and pivoting it to portrait or landscape mode.

Dual Input

Connectors to accommodate input of both analog VGA and digital DVI signals.

Embedded power supply

A power adaptor built into the body of a display device that replaces a bulky external power adaptor.

Cable management

A system for organizing cables and wires required for the operation of a display device.

Fast response time

The amount of time it takes for a liquid crystal cell to go from active (black) to inactive (white) and back to active (black) again. It is measured in milliseconds. Lower numbers mean faster transitions and therefore result in fewer visible image artifacts.

Screen tilt and swivel

Movement of a screen to attain the ideal viewing angle.

Lower power consumption

Reduction of the electrical power required to operate a device.

Kensington anti-theft lock

A security device that fixes the monitor in place to prevent theft.

VESA mounting holes

A unified industry standard for mounting IT equipment set by the Video Electronics Standards Association.

FlexiHolder

A slim groove that improves efficiency by holding reminder notes, documents, name cards, and photos on the top of monitor.

In-box DVI cable

A DVI cable is shipped with product.

Built-in Speakers

Audio speakers built into a display device.

130 mm 50.000 hrs 20 % - 80 % • Temperature Range (Operation) +5°C to +40°C

Energy Star, NUTEK 33 W (Typical)

Amber Ruilt_in 1 W

375 mm -20°C to +60°C 7.3 kg

Oberation, Green: Stand by/Sleep,

201 mm 492 mm